

Backwashing Filters with Clack WS125 Valves



Superior flow rates at a low cost

Water Filters with Clack WS125 control valves provide extremely high service flow rates at the right price. Check out the specifications, features, benefits and options described below.

Specifications

Valve	Clack WS125 valve
Electrical	120 Volt 60 Hz standard
Valve body	Glass reinforced Noryl®
Distributor	1.32" O.D.
Types	Time clock initiated
Connection	1.25" MNPT Noryl® Standard
Mineral Tank	Corrosion resistant FRP
Media	Micro-Z or Coconut Shell Carbon

Features & benefits

- Economical pricing and top quality components.
- Attached 24 volt transformer included.
- Up to 2.5 CF fully assembled, ready for installation.
- Models for capacities up to 10 cubic feet.
- Advanced digital control with diagnostics.
- Decorative mineral tank jacket options available.
- Multiple ¾" to 1½" bypass and connection options.

Meter initiated models

Part Number	Media Cu. Ft.	Media Type	Mineral Tank size	Estimated Peak GPM	Rec. GPM Range	Height (Inch)	Ship Wt. (lbs)
WST-FGA1209T	1	GAC	9x48	14	1.3-3	61	80
WST-FGA1210T	1.5	GAC	10x54	16	1.6-4.5	67	105
WST-FGA1212T	2	GAC	12x52	18	2.3-6	65	145
WST-FGA1213T	2.5	GAC	13x54	18	2.8-7.5	67	160
WST-FGA1214T	3	GAC	14x65	20	3.2-9	77	200
WST-FGA1216T	4	GAC	16x65	20	4.2-12	77	265
WST-FGA1218T	5	GAC	18x65	20	5.3-15	80	310
WST-FGA1221T	6	GAC	21x62	20	7.2-18	76	365
WST-FGA1224T	8	GAC	24x60	24	9.4-22	74	545
WST-FGA1224TC	10	GAC	24x72	24	9.4-22	85	625
WST-FMM1209T	1	Micro-Z	9x48	9	1.3-9	61	110
WST-FMM1210T	1.5	Micro-Z	10x54	10	1.6-10	67	140
WST-FMM1212T	2	Micro-Z	12x52	15	2.3-15	65	200
WST-FMM1213T	2.5	Micro-Z	13x54	16	2.8-16	67	230
WST-FMM1214T	3	Micro-Z	14x65	20	3.2-20	77	310
WST-FMM1216T	4	Micro-Z	16x65	20	4.2-20	77	425
WST-FMM1218T	5	Micro-Z	18x65	22	5.3-22	80	590
WST-FMM1221T	6	Micro-Z	21x62	22	7.2-22	76	685